

The Olight ION is a brand-new flashlight design in limited edition titanium to commemorate Olight's 10year anniversary.

This flashlight has a rectangular structure including a titanium alloy frame, gorilla glass front and back, and two TIR optic lens that run parallel delivering a balanced output of 1~320 lumens.

There are pressure sensors in the "+" and "-" areas which allow the user to select either preset brightness levels or a gradual custom brightness setting.

The ION has a built-in rechargeable LiPo battery that can be charged through the Micro-USB port located on the side of the flashlight.

The ION also includes a metal ring on its tail which can be connected to a key ring for simple and convenient carry.

The limited-edition titanium Olight Ion is the perfect gift this holiday season with it's custom brightness level settings and premium look and feel.

GENERAL DATA		
Beam Distance (ft)	180	
Beam Distance (m)	55	
Max. Performance (lumens)	320	
Charge Type	Micro-USB	
Powered By	Customised LiPo Battery	
Light Intensity (candela)	750	
Light Form	Soft and balanced beam	
Lens / Reflector Type	TIR reflector (big, defined wide hotspot)	
Mode Operation	Side switch and touch panel	
Form/Size Factor	Small size (Car key / Zippo Lighter)	
Series	Series I (Keychain)	
Unique Characteristics	 First flashlight in the world that uses a glass control panel in a 1mm thin frame. First flashlight in the world that controls the output through built-in pressure sensors under a glass control panel. Single press to select from four preset brightness levels, or press and hold for a custom output. Remaining battery power indicator: green (>75%), yellow (15%~75%) or red (<15%). Charging status indicator: red (charging), green (charging completed) both positioned on the "O" letter on the center of the panel. TIR optic lens used for soft and balanced close-range illumination. ON/OFF slide power switch located on the side for quick power control. 	
LIGHTING LEVELS		
LEVEL 1 (lumens)	320	
Run-time LEVEL 1	27m	
LEVEL 2 (lumens)	160	
Run-time LEVEL 2	1h	
LEVEL 3 (lumens)	40	
Run-time LEVEL 3	4h	
LEVEL 4 (lumens)	10	
Run-time LEVEL 4	16h	
LEVEL 5 (lumens)	2,5	
Run-time LEVEL 5	45h	
LEVEL 6 (lumens)	1	
Run-time LEVEL 6	90h	

Strobe No

GENERAL DATA	
SOS / BEACON	No
TECHNICAL CHARACTERISTICS	
Waterproof	IPXO
Weight (g / oz)	32/1.13
Length (mm / in)	58 / 2.28
Head Diameter (mm / in)	11/0.43
Body Diameter (mm / in)	27.5 / 1.08
Light Source	2 x Cree XP-G3
Packaging	Lid and base box
Use	keychain, everyday carry, gift
In The Box	 Flashlight Olight ION x 1 Connection Ring x 1 Keychain x 1 Replacement Anti-Scratch Protective Film x 2 50cm Micro-USB Cable x 1 Buit in rechargeble 300mAh 3.7V LiPo Battery
List Price	\$59.95 USD

List Price Ş59.95 USD















