

# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight

## 1000m beam distance portable LED flashlight

The M3XS-UT Javalot offers up to a full kilometer of beam distance and features a large diameter reflector with a dedomed CREE XP-L LED. The light has four brightness levels from 3 to 1200 lumens plus a strobe mode. The M3XS-UT is powered by 3 x CR123A or 4 x CR123A lithium batteries or 2 x 18650 lithium ion batteries with the included extension tube. The M3XS-UT has a brand-new strengthened conductive tail cap switch which diameter is 18mm for tactical operation, providing more reliability and more durability. M3XS-UT Javalot is ideal for hunting, search and rescue, law enforcement, outdoors and emergency preparedness.





# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight

## Light-weight, easy operation

255g, single row batteries in series structure, body diameter only 25mm The tail switch diameter is 18mm. The tail switch has a momentary ON-OFF functionality, supporting high output and strobe mode at the same time. The light brightness level and strobe mode can be activated through the side switch. Both switches are easy operation.





# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight

## Flat and low-profile side switch

The M3XS-UT Javelot features a flat and low-profile side switch with a red power indicator that glows when the flashlight runs out of power. The light level or strobe mode can be activated through the side switch.

When the battery power indicator is constantly on, the battery is out of power and the light will shut off.





# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight

WATERPROOF



IPX8

## IPX8 (waterproof up to 2 meters)

Withstands incidental exposure to water of up to 2 meters for up to 30 minutes.

Appropriate usage: indoor/outdoor use in the presence of rain, snow or brief splashes of water.



QUALITY

5

YEAR  
WARRANTY  
PROMISE



# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight



Customized holster for  
the M3XS-UT Javelot







# M3XS-UT JAVELOT

Extended-range variable-output LED flashlight

## Specifications

	Mode1	Mode2	Mode3	Mode4
	1200~720 lumens	600 lumens	80 lumens	3 lumens
	5 + 55 minutes	1.5 hours	12 hours	360 hours

Strobe Mode: 10Hz, 1200lumens

The specifications claim to ANSI/NEMA FL1-2009 Standards.  
Tests are performed with 3 x CR123A 1500mAh batteries.



extended Tube



M3XS-UT

	1000 m
	250,000 cd
	IPX8
	1m
	CREE XP-L high Intensity
	3xCR123A Or 4xCR123A, 2x18650 (With protection board)
	Flashlight: (L)211mm x head(D)63 mm
	255g (excluding batteries)
	6061-T6 Aluminium alloy structure Type III hard anodizing

