



"Disclaimer: This chart is not endorsed or affiliated in any way by Dongguan Olight E-Commerce Technology Co., Ltd. or any of its partners or subsidiaries."

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>imini</b>	3xLR41 -----	10(30m)	27	10/33	35/1.38	13.8/0.54	13.8/0.54	-----	-----	-----	11.3/0.4	6	14.95 BK, RD
<b>i1R 2 EOS</b>	Proprietary 70mAh 3.7V Micro USB Charge	150 (15m)-(50%), 5(6h)-(50%)	400	40/131	44/1.73	14.8/.58	14.8/.58	-----	N	N	13/.46	8	17.95 BK, DT 19.95 RD, GG, PU, MG, BL, PK, GN, OR
<b>i1R 2 Pro</b>	Proprietary 10220 130mAh 3.7V USB C Charge	180(23m)-5(12h)	580	48/157	51.3/2.02	16.2/.64	16.2/.64	-----	N	N	22/.78	8	21.95 BK, BL, OR, DR, S&S
<b>i3E EOS</b>	AAA -----	90 (45mAAA or 70mNIMH)	500	44/144	60.5/2.38	14/.55	12.5/.49	-----	N	N	19.4/.68	8	9.95 BK 11.95 BL, OR
		Silver Only-120(35mAA or 60mNIHM)	590	48/157	60.5/2.38	14/.55	12.5/.49	-----	N	N	19.4/.68	8	(No Price Info Older 2017 Models - PU, GN, BL, RD, DT, CU, SI)
<b>i3T EOS</b>	AAA -----	180(21m), 5(16h)	900	60/196	89/3.5	15/.59	15/.59	T	N	N	41/1.45 39/1.40 39/1.40  71/2.51 75/2.65 76.5/2.7 52/1.83 50/1.76	8	19.95 BK 19.95 MS 21.95 DT, OD, RD, BL, OR, PC 24.95 SST 29.95 BR 29.99 CU 36.95 Ti 129.95 TiD

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>i3T Plus</b>	2xAAA -----	250(1m)-100(480m), 15(28h)	1240	250/820	133/5.24	15/.59	15/.59	T	N	N	62/2.19  95.9/3.38	8	29.95 BK 32.95 BL 49.95 ANB(CU)
<b>i3UV EOS</b>	AAA -----	3.95nm UV(40m)	350mW	-----	60.5/2.38	14/.55	12.5/.49	T	N	N	19.4/.68	8	14.95 UV(OD)
<b>i5T EOS</b>	AA -----	300(3m)-150(25m)- 30(122m), 15(20h)	910	60/196	95/3.74	17.8/.7	17.8/.7	T	N	N	60/2.12  101.5/3.6 105/3.7 76/2.68 76/2.68	8	29.95 BK, BKS 32.95 OD, GG, PU, SD, CA, BL, DT 39.95 BR 39.95 CU 49.95 Ti 199.95 TiD
<b>i5T Plus - Knurling Finish or Peeble Finish</b>	2xAA -----	550(3m)-300(30m)- 55(130m), 15(54h)	1900	87/285	145/5.71	17.8/0.7	17.8/0.7	T	N	N	89/3.14	8	39.95 BK(WW,NW,CW), BL(WW,NW,CW), OR(WW,NW,CW), ODG(WW,NW, CW)
<b>i5R EOS</b>	1420mAh 14500 2.4V or AA USB C Charge	350(10m)-150(170), 15(37h)	1038	64/210	95.4/3.76	17.8/0.7	17.8/0.7	T	N	N	60/2.12 60/2.12  83/2.93 73/2.58	8	35.95 BK, OR, RRG 39.95 OD, PL, FG, ZG(NW,CW) 45.95 CU 69.95 Ti

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>i5UV EOS</b>	AA -----	365nm UV(45m)	1500mW	-----	95/3.74	17.8/.7	17.8/.7	T	N	N	63/2.22	8	32.95 UV(BM)
<b>iXV</b>	Proprietary 130mAh 10220 3.7V USB C Charge	180(23m), 5(12h)	580	48/157	51.3/2.02	-----	16.2/0.64	----	N	N	22/0.78 30.7/1.08	8	21.95 CB 39.95 Ti
<b>X9R Cell</b>	CR425 28mAh 3V -----	2.5(30h)	1	2/6.5	35/1.38	11/.43	8.9/.35	----	N	N	4.5/.16	8	15.95 BK
<b>M1T Raider Plus</b>	2xCR123A -----	800(5m)-400(120m), 15(65h)	3720	122/400	121.5/4.78	21/.83	21/.83	T	Y	N	86/3.03	8	59.95 DT
<b>M2R Warrior</b>	3500mAh 18650 Magnetic Charge MCC1A	1500(3m)-700(2h), 250(6hr15m), 60(20h), 15(70h), 1(25d)	10880	208/682	130/5.12	25.4/1.00	24.4/.96	B	Y	N	149/5.26 276/9.74	8	89.95 BK 129.95 CU
<b>M2R Pro Warrior</b>	5000mAh 21700 Magnetic Charge MCC3	1800(4.5m)-750(145m)- 250(45m), 750(160m)- 250(40m), 250(10h), 60(40h), 15(130h), 1(50d)	22400	300/984	136.5/5.37	29.5/1.16	26.2/1.03	B	Y	N	179/6.31	8	109.95 BK 119.95 DT, BL, OR, PE, GG, OD, CA, OC, ABC, WH, PU

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>S1R Baton II</b>	550mAh IMR16340 Magnetic Charge MCC1A	1000(1.5m)-300(37m), 600(1.5m)-300(45m), 60(3h40m), 12(20h), 0.5(8d)	5250	145/476	63/2.48	21/.83	21/.83	S	Y	N	51/1.8  62/2.19 -----	8	64.95 BK 69.95 DT, RD, OR, PE, PU, BL, LC, VR, (PB-Not For Sale At This Time) 79.99 CU 99.95 Ti (Spring, Summer, Autumn, Winter)
<b>S2R Baton II</b>	3200mAh 18650 Magnetic Charge MCC1A	1150(2m)-400(230m), 400(4h), 120(14h), 15(100h), 0.5(60d)	4600	135/443	100/3.94	23/.91	23/.91	S	Y	N	98.5/3.47  162/5.73	8	69.95 BK 74.95 DT, GN, PU, WH, LC, LG(NW,CW) 109.95 Ti (Honor, Courage, Freedom, Peace) 89.95 CU
<b>S30R III Baton</b>	3500mAh 18650 Magnetic Charge MCC1A	1050(2m)-500(200m), 500(210m), 120(15h), 12(130h), 0.5(100d)	8840	188/616	114/4.48	25.3/.99	21.5/.84	S	Y	N	110/3.88	8	79.95 BK
<b>Baton Pro</b>	3500mAh 18650 Magnetic Charge MCC1A	2000(1m)-600(160m), 600(210m), 120(810m), 30(55h), 5(9d)	4350	132/433	108/4.25	25/.98	24/.94	S	Y	N	107/3.77  133/4.69	8	89.95 BK 94.95 DT 99.95 BL 129.95 Ti

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Baton 3</b>	550mAh 3.7V IMR16340 Magnetic Charge MCC1A	1200(1.5m)-300(75m), 300(95m), 60(7.5h), 12(33h), 0.5(20d)	6889	166/544	63/2.48	21/.83	21/.83	S	Y	N	53/1.87 86/3.03 91/3.2 64/2.26	8	64.95 BK, RD 69.95 SST 74.95 PG, SI, DB 99.95 Eternal (CU) 109.95 Ti (Spring, Summer, Autumn, Winter)
<b>Baton 3 Premium - With Charging Case</b>	550mAh 3.7V IMR16340 (Charger Case-3500mAh 3.6V 18650-Charge up to 3.7x) Magnetic Charge - USB C Charge For Case (MCC1A For Baton 3)	1200(1.5m)-300(75m), 300(95m), 60(7.5h), 12(33h), 0.5(20d)	6889	166/544	63/2.48, Charging Case- 62x30x83.5mm/ 2.44x1.18x3.29 in	21/.83	21/.83	S	Y	N	53/1.87 (Charger Case 114/4.02)  91/3.2 64/2.26	8	99.95 BK, RD 109.95 BL, OR, PG, PE, 5OD, WH, SI, DB 119.95 DP 139.95 Eternal (CU) 149.95 Ti (Spring, Summer, Autumn, Winter)
<b>Seeker 2</b>	5000mAh 21700 Magnetic Charge MCC1A	3000(3m)-600(155m), 1200(110m)-600(50m), 300(13h), 50(72h), 5(15d)	12100	220/772	126/4.96	35/1.38	27.5/1.08	S	Y	N	185/6.53	8	109.95 BK 119.95 BL
<b>Seeker 2 Pro</b>	5000mAh 21700 Magnetic Charge MCC1AL	3200(2m)-600(150m), 1200(110m)-600(30m), 300(9h30m), 50(52h), 5(12d)	15600	250/820	128/5.04	35/1.38	28/1.1	S	Y	N	198/6.98	8	139.95 BK, AB 149.95 DT, MG, OR, BL, CF, OD

<u>Model</u>	<u>Battery/ Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/ Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Seeker 3</b>	4000mAh 21700 3.6V Magnetic Charge MCC3	3500(2.5m)-1200(87m)- 600(37m), 1200(96m)- 600(37m)-300(9m), 300(9h), 50(47h), 5(12d)	12100	220/722	128/5.04	35/1.38	27.5/1.08	S	Y	N	184/6.49	8	109.95 BK 119.95 OD
<b>Seeker 3 Pro</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	4200(2.5m)- 1200(127m)-600(35m), 1200(135m)-600(35m)- 300(10m), 300(640m), 50(55.5h), 5(15d)	15625	250/820	132/5.20	35/1.38	28/1.10	S	Y	Y	200/7.05	8	139.95 BK, S&S 149.95 DT, OR, OD, LB, FG 159.95 NW
<b>R50 Pro Seeker</b>	4500MAh 26650 Magnetic Charge MCC5V	3200(1.5m)- 1000(150m), 1500(10m)- 1000(160m), 400(7.5h), 60(50h)	15600	250/820	128/5.03	42/1.65	32/1.25	S	Y	N	262/9.24	8	139.95 BK
<b>Warrior Mini</b>	3500mAh 18650 Magnetic Charge MCC3	1500(4m)-500(205m)- 170(55m), 500(218m)- 170(50m), 120(18h), 15(130h), 1(45d)	9025	190/630	106.5/4.19	23/.91	23/.91	B	Y	N	105/3.7 171/6.03 124/4.37	8	79.95 BK, DT 89.95 RD, CA 99.95 CU (Eternal) 119.95 Ti (Spring, Summer, Autumn, Winter)

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Warrior Mini 2</b>	3500mAh 3.6V 18650 Magnetic Charge MCC3	1750(4m)-500(206m)- 200(40m), 500(218m)- 200(55m), 120(19h), 15(164h), 1(45d)	12300	220/722	118/4.65	25/.98	23/.91	B	Y	Y	122/4.3 194/6.86 145/5.1 189/6.67	8	89.95 BK, DT, S&S 94.95 MS, WH, OR, OD, RB 109.95 CU 139.95 Ti (Fire, Water, Air, Earth, Ofan Day) BR-Black Diamond Gift (No Price)
<b>Warrior 3</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	2300(2.5m)-800(160m)- 250(39m), 800(166m)- 250(39m), 200(15h), 15(130h), 1(55d)	23000	300/984	139/5.47	29.5/1.16	26.2/1.03	B	Y	N	176/6.21	8	119.95 BK 129.95 DC, OR, SG
<b>Warrior 3S</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	2300(2.5m)-800(160m)- 250(39m), 800(166m)- 250(39m), 200(13h), 15(130h), 1(55d)	23000	300/984	139/5.47	29.5/1.16	26.2/1.03	B	Y	Y	176/6.21 304/10.72	8	124.95 BK, GG 139.95 CU
<b>Warrior 3S Titanium</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	1850(2.5m)-650(235m)- 250(29m), 650(240m)- 250(26m), 200(13h), 15(130h), 1(55d)	16900	260/853	139/5.47	29.5/1.16	26.2/1.03	B	Y	Y	214/7.55	8	159.95 Air, Earth, Fire, Water
<b>Warrior X</b>	3000mAh 18650 Magnetic Charge MCC1A	2000(1.5m)-600(80m), 300(4h40m)	78400	560/1837	142/5.59	41/1.61	25.4/1.01	T	Y	N	218/7.69	8	129.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Warrior X 3</b>	5000mAh 21700 Magnetic Charge MCC3	2500(2.5m)- 1000(129m)-300(13m), 300(8h)	78000	560/1837	149.5/5.89	39/1.54	26.2/1.03	T	N	N	255/8.99	8	129.85 BK 139.95 OD, DC
<b>Warrior X Pro (Old Version Pre 10-2020)</b>	5000mAh 21700 Magnetic Charge MCC3	2250(2m)-1000(100m)- 300(23m), 300(8h)	90000	600/1969	149/5.87	39/1.54	26.2/1.03	T	N	N	239/8.43	8	129.95 BK 139.95 DT, OD, GG, CA
<b>Warrior X Pro (New Version 10-2020)</b>	5000mAh 21700 Magnetic Charge MCC3	2100(2m)-1000(100m)- 300(23m), 300(8h)	62500	500/1640	149/5.87	39/1.54	26.2/1.03	T	N	N	239/8.43	8	119.95 BK 129.95 GN, RD, BL, DS, OD, WH
<b>Warrior X Turbo</b>	5000mAh 21700 Magnetic Charge MCC3	1100(6.5m)-600(105m)- 300(27m)-150(52m), 150(12.5h)	250000@1100L / 32400@150L	1000/3280	157/6.18	58/2.28	26.2/1.03	T	N	N	294/10.37	8	139.95 BK 149.95 DT, GG, DC, GC 151.95 LC
<b>Javelot Pro</b>	2x 3500mAh 18650 Magnetic Charge MCC5V	2100(10m)- 1000(130m), 600(5h), 150(23h), 15(8d)	291600	1080/3543	247/9.72	63/2.48	26/1.02	B	N	N	380/13.4	8	199.95 BK
<b>Javelot Pro 2</b>	2x5000mAh 21700 3.6V Battery Pack Magnetic Charge MCC3	Turbo 2500(5m)- 1000(180m)-600(27m), High 600(420m)- 150(42m), Med 150(32.5h), Low 15(12d)	217400	1050/3445	259/10.2	63/2.48	26/1.02	B	N	N	423/14.92	8	209.95 BK 229.95 DC



<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Javelot Turbo</b>	2x 5000mAh 21700 Magnetic Charge MCC3	1300(10m)-800(140m)- 500(30m)-150(110m), 500(350m)-150(130m), 150(27h), 15(318h)	422500	1300/4265	259/10.2	63/2.48	25.8/1.02	B	N	N	408/14.4	8	229.95 BK 239.95 DT
<b>Marauder 2</b>	3x 5000mAh 21700 USB C Charge	Flood - 14400(5m)- 3200(140m)-1600(45), 6400(13m)-3200(120m)- 1600(40m)-800(22m), 3200(90m)-1600(90m)- 800(10m)-400(10m)- 200(70m), 1600(450m), 800(13h), 400(22h), 200(40h) Spotlight - 850(20m)- 650(170m)-500(85m)- 300(25m)-200(15m)- 100(85m), 650(115m)- 500(180m)-300(20m)- 200(20m)-100(85m), 500(360m)-300(25m)- 200(15m)-100(80m)- 50(110m), 300(700m), 200(19h), 100(31h), 50(59h)	160000- Flood/50600- Spotlight	Flood- 450/1476 Spot- 800/2625	140/5.51	79/3.11	53/2.09	S	Y	Y	750/26.5	8	329.95 BK 349.95 BL

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Marauder 2 With Hard Case</b>	3x 5000mAh 21700 USB C Charge	Flood - 14400(5m)-3200(140m)-1600(45), 6400(13m)-3200(120m)-1600(40m)-800(22m), 3200(90m)-1600(90m)-800(10m)-400(10m)-200(70m), 1600(450m), 800(13h), 400(22h), 200(40h) Spotlight - 850(20m)-650(170m)-500(85m)-300(25m)-200(15m)-100(85m), 650(115m)-500(180m)-300(20m)-200(20m)-100(85m), 500(360m)-300(25m)-200(15m)-100(80m)-50(110m), 300(700m), 200(19h), 100(31h), 50(59h)	160000- Flood/50600- Spotlight	Flood- 450/1476 Spot- 800/2625	140/5.51	79/3.11	53/2.09	S	Y	Y	750/26.5	8	359.95 OR, DT, OD, AB, DC, MBL
<b>X7R Marauder</b>	4x 3500mAh 18650 USB C Charge	12000(3m)-3000(120m), 7000(12m)-3000(110m), 3000(2h10m), 1000(6h), 500(14h), 10(30d)	36100	380/1247	129/5.08	68/2.67	52/2.05	S	Y	Y	665/23.46	7	279.95 BK
<b>X9 Maurauder</b>	Proprietary 6000mAh 14.4V 8x18650 Battery Pack Proprietary DC Charger Plug	25000(3m)-6400(100m), 12800(10m)-6400(90m), 6400(2h), 3200(4h), 1600(8h), 800(12h), 400(19h), 200(27h)	99200	630/2067	320/12.6	100/3.94	57/2.24	S	Y	Y	1855/65.43	7	600.00 BK 660.00 BL, OD

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Freyr</b>	5000mAh 21700 Magnetic Charge MCC3	1750(2m)-800(150m)-300(28m), 300(9.5h), 5(15d), Red-30(22h) Green-60(14h) Blue-25(12h)	32400	360/1181	136/5.35	40.5/1.59	25.6/1.01	B	Y	N	202/7.13	8	129.95 BK 139.95 OR
<b>Archer</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	1000(1m)-470(160m)-300(20m), 300(6h), 50(42h), 5(200h)	72656	535/1755	126/4.26	Head Width 36.5/1.44	Head Length 46/1.81	S	Y	N	200/7.05	7	99.95 BK
<b>Perun</b>	3500mAh 18650 Magnetic Charge MCC3	2000(2.5m)-800(160m), 500(240m), 120(15h), 30(47.5h), 5(10d), SOS(5h)	3600	120/394	112/4.41	26/1.02	23/.91	S	N (SOS)	Y	120/4.23	8	84.95 BK 92.95 BL
<b>Perun 2</b>	4000mAh 21700 Magnetic Charge MCC3	2500(2m)-800(130m)-500(45m), 500(240m)-300(30m), 120(18h), 30(66h), 5(12.5d)	6889	166/544	120.7/4.75	28.6/1.13	27/1.06	S	N (SOS)	Y	161/5.68	8	89.95 BK 99.95 PG, OR, PU, CLG
<b>Perun Mini</b>	550mAh IMR16340 Magnetic Charge MCC1A	1000(1m)-250(1h25m), 250(1h38m), 65(6h), 15(25h), 2(4.5d) - SOS(2h20m)	2500	100/328	61.5/2.42	21/.83	20.6/.81	S	N (SOS)	N	52/1.83	8	64.95 BK, DC (See Notes) 69.95 DT, OR, GYL

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Array</b>	2000mAh 3.7V Magnetic Charge MCC1A	400(2h30m), 200(4h30m), 100(6h30m), 50(13h)	1600	80/262	45x23x24mm/ 1.77x.91x.94in - Battery Pack 64.5x42.4x24 mm/2.54x1.67x .94in	-----	-----	----	N (SOS)	N	124/4.37	4	59.95 BK
<b>Array 2</b>	1600mAh 3.6V Battery Pack USB C Charge	600(3h), 250(4.5h), 100(8.5h), SOS- 600(3.5h)	2700	100/328	Headlamp 51x24x24mm/ 2.01x.94x.94in Battery Pack 78.7x31.2x28.3 mm/ 3.10x1.23x1.11in	-----	-----	S	N (SOS)	N	109/3.84	4	59.95 BK
<b>Array 2S</b>	2600mAh 3.6V Battery Pack USB C Charge	Flood+Spot 1000(4h), 500(5h), 100(13.5h) Flood 500(5h), 250(6.5h), 30(30h) Red Light 200(5.5h), 100(8.5h), 40(15h)	5000	140/459	Headlamp 61x31x24.5mm/ 2.40x1.22x.96 in	-----	-----	S	N (SOS)	N	131/4.62	4	79.95 BK 89.95 OR, MBL
<b>H05 Lite Headlamp</b>	2xAAA -----	White High 45(10m)- 25(140m), Med 20(4h), Low 5(10h) Red LED 8h, Red LED Flashing 18h	14	7/23	58.3/2.3	36.5/1.44	33.8/1.33	----	N	N	66.5/2.35	2	29.95 BL, PK
<b>H1R</b>	650mAh RCR123A Magnetic Charge MCC1A	600(3m)-180(80m), 180(100m), 60(5h), 15(20h), 2(6d), SOS(6h)	1280	72/236	61.5/2.42	21/.82	19.5/.76	S	N (SOS)	N	51.5/1.82	8	66.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>H2R</b>	3000mAh 18650 Magnetic Charge MCC1A	2300(1m)-750(110), 600(2.5h), 150(10h), 30(50h), 1(45d)	5850	153/501	110/4.33	25/.98	23.2/.91	S	N (SOS)	N	100/3.53	8	89.95 BK
<b>Olantern</b>	4x 1900mAh 3.7V 18500 Magnetic Charge MCC3	360(6.5h), 120(20h), 30(75h), 1(80h-Flame)	-----	-----	136.3/5.37 (Height)	-----	66/2.6 (Base)	S	N	N	347/12.24	4	79.95 RD, GN, GY
<b>Olantern Mini</b>	2000mAh 3.7V 26350 Magnetic Charge MCC3	150(4h), 50(12h), 15(48h), 1(Red-34h)	-----	-----	99.35/3.91 (Height)	-----	52.2/2.06 (Base)	S	N	N	239/8.43	4	59.95 BK, RD, GY 99.95 AB
<b>Olantern Classic</b>	3xAA Batteries -----	LED Module 1-Level 1 Warm Orange LED 14(78h), Level 2 Warm Orange LED 60(9h), LED Module 2 Level 1 Warm White LED 65(17h), Level 2 Warm White LED 190(4h)	-----	-----	165/6.5	-----	110/4.33	T	N	N	605/21.34	5	49.95 AB
<b>Olantern Classic 2 Lite</b>	4xAA -----	Mode 1 - Warm Orange 10(105h), Warm White 120(6h20m) Mode 2 - Warm Orange 130(3.5h), Warm White 240(20m)-150(200m)- 100(60m)	30	11/36	Height 186/ 7.32	-----	124/4.88	S	-----	-----	654/23.1	5	74.95 CLB, FG

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Olantern Classic 2 Pro</b>	3.6V 11200mAh (4x18650) Magnetic Charge USB-C or MCC3	Mode 1 - Warm Orange 10(180h), Warm White 130(35h) Mode 2 - Warm Orange 130(23h), Warm White 300(20m)-200(480m)-150(1000m)	50	14/46	Height 186/7.32	-----	124/4.88	S	-----	-----	756.6/26.69	5	99.95 AB, CLB, FG
<b>Olantern Pumpkin Cover</b>	----- -----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	9.95 OR
<b>Obulb</b>	Proprietary 630mAh 3.7V Magnetic Charge MCC1A	55(3h), 3.5(56h), 7(Steady Red-7h), 7(Flashing Red-30h)	-----	-----	48/1.89 (Height)	54/2.13	54/2.13	-----	N	N	55/1.94	7	19.95 RD, GN, GY, PK, OR, PU
<b>Obulb MC</b>	Proprietary 630mAh 3.7V Magnetic Charge MCC1A	White High 75(3h), White Low 3.5(40h), Color Fantasy 3 to 7(7h)	-----	-----	48/1.89 (Height)	54/2.13	54/2.13	-----	N	N	58/2.05	7	29.95 BK, WH, BRD, OR, PU, SB, CR, CG
<b>Obulb MCs</b>	Proprietary 630mAh 3.7V Magnetic Charge MCC1A/MCC3	White High 75(3h) White Low 305(40h) Color Fantasy 3-7(7h)	-----	-----	48/1.89	-----	54/2.13	-----	N	N	60/2.12	7	39.95 ABL, WH
<b>Obulb MC Christmas Pack</b>	Proprietary 630mAh 3.7V Magnetic Charge MCC1A	White High 75(3h), White Low 3.5(40h), Color Fantasy 3 to 7(7h)	-----	-----	48/1.89 (Height)	54/2.13	54/2.13	-----	N	N	58/2.05	7	76.95 Includes MC RD, MC GN, Obuddy RD, Santa Cover

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Obulb Pro (Bluetooth Controlled)</b>	Proprietary 1650mAh 3.7V Magnetic Charge MCC1A/MCC3	White Light High 240(2.5h), White Light Low 4.5(84h), Color Lights --(17h)	-----	-----	58/2.28	65/2.56	65/2.56	B	----	----	105/3.7	7	39.99 BK, BL, GY, ODG, OR
<b>Obuddy (Obulb Astronaut and Charger Holder)</b>	----- -----	-----	-----	-----	63x54x60mm/ 2.48x2.13x2.36 in	-----	-----	----	----	----	56/1.98	----	9.95 BL, OR RD (Only Avail in XMAS Pack)
<b>Osling</b>	----- -----	-----	-----	-----	-----	-----	-----	----	----	----	----	----	5.95 CL, PK, BL, PU, OR
<b>BFL 900 Bicycle Light</b>	2600mAh 18650 Magnetic Charge MCC1AL	900(1.5h), 450(5h), 250(13.5h)	5600	150/492	96/3.78	32/1.26	41.5/1.63	S	N	N	130/4.59	6	59.95 BK
<b>BFL 1800 Bicycle Light</b>	5000mAh 21700 Magnetic Charge MCC1AL	1800(1.5h) 1000(3.5h) 500(8.5h)	11000	210/688	102/4.02	32/1.26	41.5/1.63	S	N	N	162/5.71	6	79.95 BK
<b>RN 400 Bicycle Light</b>	Proprietary 900mAh 3.7V USB C Charge	400(1h40m), 200(3h10m), 100(6.5h), Flashing 1 0- 200(7h), Flashing 2 0- 200(5.5h)	1900	89/292	31x31x72mm/ 1.22x1.22x2.83in	-----	-----	S	N	N	85/3.0	7	29.95 BK
<b>RN 800 Bicycle Light</b>	4000mAh 21700 3.6V USB C Charge	800(2h), 400(4h), 200(8h), Flash 1 0- 400(9h), Flash2 0- 700(7h)	4700	137/449	107/4.21	31/1.22	31/1.22	S	N	N	172/6.07	6	59.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>RN 1200 Bicycle Light</b>	4000mAh 21700 3.7V USB C Charge	1200(1.5h), 600(3h), 300(6.5h), Flash 1 0- 600(7h), Flash 2 0- 900(5h)	5400	146/479	107/4.21	31/1.22	31/1.22	S	N	N	161/5.68	7	69.95 BK
<b>RN 1500 Bicycle Light</b>	5000mAh 21700 USB C charge	1500(100m), 750(4h), 300(12.5h), Flash 1 0- 750(11.5h), Flash 2 0- 750(10h)	6700	164/538	107/4.21	31/1.22	31/1.22	S	N	N	172/6.06	7	79.95 BK
<b>RN 3500 Bicycle Light</b>	5200mAh 7.2V 4x 18650 Micro USB Charge	Mode 1 [1400(4.5h), 700(8h), 300(20h), 100(75h), Flash(15.5h)], Mode 2 [1800(2.5h), 1000(4.5h), 600(8.5h), 200(19h48m), Flash(9.5h)], Mode 3 [3500(1h42m), 1800(3h12m), 900(6.5h), 350(17h), Flash 0-1800(6.5h)]	31000	350/1148	60x43.5x41.5 mm/ 2.36x1.71x1.63 in	-----	-----	S	N	N	110/3.88 W/O Battery Pack	5	199.95 BK
<b>Allty 2000 Bicycle Light</b>	2x 3500mAh 18650 Micro USB Charge	Mode 1 [55(14.5h)], Mode 2 [1000(2h), 500(3.5h), 250(5.5h), 100(10h)], Mode 3 [1000(2h), 500(3.5h), 250(5.5h), 100(10h)], Mode 4 [2000(1h), 1000(2h), 500(3.5h), 200(8.5h)], Mode 5 [1800(1h50m), 1000(3.5h), 500(5.5h), 200(10h50m)]	7000	165/541	99x42x39mm/ 3.89x1.65x1.54in	-----	-----	S	N	N	183/6.46	5	149.95 BK



<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Seeme 30 Bicycle Tail Light</b>	Proprietary 330mAh Micro USB Charge	30(2h), 14(7h), 7(9.50), Flash 7(40h), Breathe 0-30(4.5h), Comet 30-0(5.5h), Smart Mode Day 30(15.5h), Smart Mode Night 3-30(10.5h)	-----	-----	65x15x21mm/ 2.56x.59x.82in	-----	-----	S	N	N	24/.85	6	16.95 BK
<b>PL-2 Valkyrie</b>	2xCR123A -----	1200(1.5m)-600(70m)	13800	235/770	82.5/3.25	32.5/1.28	36.5/1.44	----	Y	N	115/4.06	6	99.95 BK 104.95 GG
<b>PL-Pro Valkyrie</b>	Proprietary 900mAh 3.6V Magnetic Charge MCC1A	1500(1.5m)-600(45m), 300(90m)	19600	280/918	83x36x32mm/ 3.27x1.42x1.26in	-----	-----	----	Y	N	92/3.25	6	129.95 BK, DT 139.95 GG
<b>PL-Mini Valkyrie</b>	Proprietary 960mAh Magnetic Charge MCC Special	400(1m)-60(70m)	1400	75/246	61.2/2.41	31.2/1.23	26.9/1.06	----	N	N	62/2.19	6	79.95 BK
<b>PL-Mini Valkyrie 2</b>	Proprietary 260mAh 3.7V Magnetic Charge MCC Special	600(1m)-60(1h)	2500	100/328	52.5/2.07	32/1.26	32.5/1.28	----	N	N	73/2.57 91/3.21	6	89.95 BK, DT, OD, MBK 94.95 GG 199.95 Ti
<b>Valkyrie IR</b>	Proprietary 320MAh 3.7V Magnetic Charge MCC Special	400(1m)-100(82m), IR 150mW(2h)	6000	150/492	52.5x32.8x35.8 mm/ 2.1x1.29x1.41in	-----	-----	----	N	N	79/2.79	6	109.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Valkyrie Turbo (LEP)</b>	2x 1600 mAh CR123A -----	250(4m)-60(180m)	70225	530/1738	90.1/3.55	Height 33.7/1.33	Width 36.6/1.44	----	N	N	133/4.7	6	149.95 BK, DT
<b>PL-2RL Baldr</b>	2xCR123A -----	Mode 1 Laser Off 1200(1.5m)-400(105m) Laser On 1200(1.5m)- 400(100m), Mode 2 Laser Off 400(2h), Laser On 400(105m), Laser Only (75h)	13800	235/771	83.7x36.5x47 mm/ 3.3x1.44x1.85in	-----	-----	----	Y	N	137/4.28	6	129.95 BK
<b>Baldr RL</b>	2xCR123A -----	Laser Off 1120(1m)- 500(125m), 300(4h), Laser On 1120(1m)- 500(2h), 300(3h45m), Laser(75h)	14400	240/787	84x36.5x44.5 mm/ 3.3x1.44x1.75in	-----	-----	----	Y	N	129/4.55	4	129.95 BK, DT 139.95 GG
<b>Baldr Pro (GL)</b>	2xCR123A -----	Laser Off 1350(1m)- 500(125m), 300(4h), Laser On 1350(1m)- 500(1h55m), 300(3.5h), Laser(45h)	16900	260/853	84x36.5x44.5 mm/ 3.3x1.44x1.75in	-----	-----	----	Y	N	129/4.55	4	149.95 BK, DT, MBK 159.95 OD, GG, MBL

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Baldr Pro R</b>	Proprietary 1000mAh 3.6V Magnetic Charge MCC1A	Light+Laser (High Mode) 1350(1.5m)-500(38m)-300(10m), Light+Laser (Low) 300(85m) Light Only (High) 1350(1.5m)-500(40m)-300(13m), Light Only (Low) 300(93m), Laser Only 5mW(19h)	10000	200/656	95x36.6x34.1 mm/ 3.74x1.44x1.34in	-----	-----	----	Y	N	126/4.44	4	169.95 BK, DT 179.95 GG
<b>Baldr RL Mini</b>	Proprietary 230mAh 3.7V Magnetic Charge MCC Special	Laser Off 600(1m)-100(39m), Laser On 600(1m)-100(37m), Laser(11h)	4225	130/426	57x32.8x35.8 mm/ 2.24x1.29x1.41in	-----	-----	----	N	N	91/3.21	4	109.95 BK 119.95 DT
<b>Baldr Mini (GL)</b>	Proprietary 230mAh 3.7V Magnetic Charge MCC Special	Laser Off 600(1m)-100(39m), Laser On 600(1m)-100(29m), Laser(2.5h)	4225	130/426	57x32.8x35.8 mm/ 2.24x1.29x1.41in	-----	-----	----	N	N	87/3.07	4	129.95 BK, DT 139.95 GG
<b>Baldr S (GL)</b>	Proprietary 380mAh 3.7V / Laser 5mW(510-520nm) Magnetic Charge MCC Special	Laser Off 800(1m)-300(2m)-100(37m), 100(140m) Laser On 800(1m)-300(2m)-100(30m), 100(90m), Laser(5h)	4400	130/426	63/2.48	32.5/1.28	36/1.42	----	N	N	95/3.35	4	129.95 BK, DT, MBK 139.95 GG, BL

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Baldr S BL</b>	Proprietary 380mAh 3.7V / Laser 5mW(440-460nm) Magnetic Charge MCC Special	Laser Off 800(1m)-300(2m)-100(40m), 100(140m) Laser On 800(1m)-300(2m)-100(38m), 100(130m), Laser(21h)	4400	130/426	63/2.48	32.5/1.28	36/1.42	----	N	N	95/3.35	4	129.95 BK
<b>Baldr IR</b>	2xCR123A	1350(1m)-500(78m)-300(20m), 300(4h), IR 850nm(80h)	1350	260/853	84x36.5x44.5 mm/ 3.3x1.44x1.75in	-----	-----	----	N	N	129/4.55	4	159.95 BK
<b>Odin Mini</b>	2040mAh 18500 Magnetic Charge MCC3	1250(6m)-900(11m)-700(39m)-200(14m), 200(5h)	14400	240/787	115.5/4.55	29/1.14	25.7/1.01	T	N	N	176/6.21	8	139.95 BK, DT 149.95 GG
<b>Odin</b>	5000mAh 21700 Magnetic Charge MCC3	2000(2m)-1000(9m)-760(125m)-300(24m), 300(8h)	22500	300/984	136.5/5.37	29/1.14	26.6/1.05	T	N	N	216/7.62	8	159.95 BK 169.95 GG, DT, RD
<b>Odin Turbo (LEP)</b>	5000mAh 21700 Magnetic Charge MCC3	330(30m)-180(2.5h)-90(30m), 90(7.5h)	275625	1050/3445	155/6.1	31/1.22	27/1.05	T	N	N	249/8.78	8	249.95 BK 259.95 DT
<b>Odin IR</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	Light High 1000(3m)-450(165m)-200(22m)-120(33m) Light Low 200(493m)-120(35m) IR High 850nm 150mW(22.5h) IR Low 850nm 30mW(91h)	38960(H)/8528(L)	400/1312	137.5/5.41	29/1.14	26.6/1.05	B	N	N	217/7.65	8	169.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Odin GL M</b>	5000mAh 21700 3.6V Magnetic Charge MCC3	Light High Laser On 1500(2.5m)-550(155m)- 300(15m) Light Low Laser On 300(360m) Light High Laser Off 1500(2.5m)-550(168m)- 300(20m) Light Low Laser Off 300(390m)	11556	215/705	149/5.87	29/1.14	26.6/1.05	T	N	N	224/7.90	4	209.95 BK
<b>Odin GL Mini</b>	18500 2040mAh 3.6V Magnetic Charge MCC3	Laser and Light On High 1000(3.5m)-500(61m)- 200(12m), Low 200(195m) Light Only High 1000(3.5m)-500(67m)- 200(13m), Low 200(215m)	8100	180/591	128/5.04	29/1.14	26.6/1.05	T	N	N	190/7.62	4	189.95 BK
<b>O Pen2</b>	Proprietary 110mAh 3.7V USB C Charge	120(20m), 60(40m)- 50(10m), 20(2h)- 15(20m), 5(8h)-3.5(2h)	64	16/52.5	145/5.71	-----	12.7/.5	-----	N	N	38/1.34 32/1.13 47.6/1.68 77/2.72 59.8/2.11	-----	49.95 BK 59.95 BL, GG, DT, SS 64.95 Ti 64.95 CU 199.95 ZR

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Open Pro</b>	Proprietary 110mAh/(Laser)407mWh 3.7V USB C Charge	120(23m), 60(40m)- 10(5m), 20(2h), 5(8h), Laser(4.5h)	49	14/46	153/6.02	-----	12.7/.5	----	N	N	35/1.23 72.3/2.55 67.4/2.38 43.6/1.54 48.2/1.7	----	69.95 BK 74.95 BL, PU, OR, ER, DB 89.95 CU 89.95 BB 99.95 Ti 299.95 ZD, ZDSS
<b>Open Mini (No Light)</b>	----- -----	-----	-----	-----	93/3.66	-----	9.8/0.39	----	----	-----	12.5/0.44	----	12.95 BK, OR, BL ODG-Bundle Only
<b>Swivel COB Work Light</b>	Proprietary 2600mAh USB C Charge	COB (Flood) 400(5h), 160(9h), 12(90h) Flashlight 200(5h), 50(27h)	N/A	25/82-COB 80/262- Flashlight	123x51x35mm /4.84x2.01x1.38 in	-----	-----	S	N	N	180/6.35	4	34.95 BK, OD, OR 39.95 BL, YL
<b>Olamp Nightour</b>	Stem - 4000mAh 3.7V Lamphead - 100mAh 3.7V Stem - USB C Charge Lamphead - Magnetic Charge MCC3	Stem - White High 60(4h20m), White Low 8(31h), RGB Mode 1 2- 10(13h), RGB Mode 2 2- 10(15h) Lamphead - White High 90(15m), White Low 1(10.5h)	-----	-----	Stem - 396.4/15.61 Lighthead - 37.4/1.47	-----	Stem - 85/3.35 Lighthead - 33.2/1.3	B	N	N	Stem - 420/14.82 Lighthead - 45/1.59	----	99.95 BK
<b>Oknife Beagle</b>	Blade-154CM SS Handle-G10 Handle-Micarta	-----	-----	-----	Overall 193/7.6	Blade 85/3.3	Handle 108/4.3	----	----	-----	G10 97.3/3.44 MI 96.7/3.41	----	75.95 BK 79.95 OG

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Oknife Chital</b>	Blade-D2 Steel Ti Coated Handle-G10	-----	-----	-----	Overall 191.8/7.55	Blade 81.3/3.2	Handle 110.5/4.35	----	----	----	92/3.25	----	49.95 BK
<b>Oknife Mini Chital</b>	Blade-D2 Steel Ti Coated Handle-G10	-----	-----	-----	Overall 165.1/6.5	Blade 69.9/2.75	Handle 95.2/3.75	----	----	----	65/2.29	----	49.95 BK
<b>Oknife Drever</b>	Blade-N690 SS Handle-G10	-----	-----	-----	Overall 203/7.99	Blade 88.6/3.49	Handle 114.4/4.5	----	----	----	96.9/3.42	----	69.95 BK, BL, OR, WH
<b>Oknife Drever Stars and Stripes Handle Only</b>	----- Handle-Aluminum Alloy	-----	-----	-----	-----	-----	Handle 114.4/4.5	----	----	----	----	----	35.95 S&S
<b>Oknife Mini Drever</b>	Blade-N690 SS-Ti Coated Handle-G10	-----	-----	-----	Overall 154.1/6.07	Blade 63.5/2.5	Handle 90.6/3.57	----	----	----	68.7/2.42	----	65.95 BK
<b>Oknife Parrot</b>	Blade-154CM SS Handle-Micarta (Black) or Handle-G10 (Grey)	-----	-----	-----	Overall 159/6.3	Blade 67/2.6	Handle 92/3.7	----	----	----	100.7/3.55 93.4/3.3	----	74.95 GY (G10) 79.95 BK (Micarta)
<b>Oknife Ratel</b>	Blade-154CM SS Handle-G10	-----	-----	-----	Overall 190.1/7.48	Blade 81.3//3.2	Handle 108.8/4.28	----	----	----	112.2/3.96	----	74.95 BL
<b>Oknife Splint</b>	Blade-N690 SS Handle-G10	-----	-----	-----	Overall 176/6.93	Blade 75.31/2.97	Handle 100.69/3.9	----	----	----	80.2/2.83	----	69.95 BK, GY

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Oknife Splint Titanium</b>	Blade-CPM-S35VN SS Handle-TC4 Titanium Alloy	-----	-----	-----	Overall 176/6.93	Blade 75.31/2.97	Handle 100.69/3.9	----	----	----	67.7/2.39	----	169.95 Ti
<b>Oknife Zilla</b>	Blade-154CM SS Handle-G10	-----	-----	-----	Overall 212.5/8.37	Blade 88.5/3.48	Handle 124/4.88	----	----	----	151.8/5.35	----	84.95 GN
<b>Oknife Nightclaw EDC</b>	Blade-D2 Steel Handle-G10	-----	-----	-----	Overall 79.7/3.14 Blade 23.3/.92 Handle 56.4/2.22	Handle Diam. 40.1/1.58	Handle Thick. 11.5/.45 Blade Thick. 3.0/.12	----	----	----	38/1.34	----	39.95 BL, DT
<b>Oknife Otacle - EDC Utility Knife</b>	Blade-SK2 Steel Handle-G10	-----	-----	-----	85.8/3.38	Width 32.7/1.29	Height 6.8/0.27	----	----	----	54.7/1.93	----	16.95 BL, ODG
<b>Oknife Otacle 2 - Titanium Pry Bar With Copper Inlay</b>	Body-Ti Inlay-CU	-----	-----	-----	114.7/4.52	Width 22/0.87	Height 9.4/0.37	----	----	----	50/1.76	----	39.95 Ti
<b>OreMake 8-inch KIRITSUKE Chef Knife</b>	Blade-T-CO69 Damascus Steel Handle-G10	-----	-----	-----	N/A	Blade 203.2/8.0		----	----	----	252/8.9	----	99.95 BK
<b>OreMake 7-inch NAKIRI Chef Knife</b>	Blade-T-CO69 Damascus Steel Handle-G10	-----	-----	-----	N/A	Blade 177.8/7.0		----	----	----	N/A	----	99.95 BK



<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>OSTATION Portable Power Station</b>	11.1 Volt/230.88Wh AC Adapter (Full Charge in 6h)	Output: 1-USBC, 3-USBA, 1-DC (Cigarette Lighter), 1-AC (3 Prong Outlet)	-----	-----	223x138x147 mm/ 8.78x5.43x5.79 in	-----	-----	----	----	-----	3260/114.99	----	199.95 BK
<b>Oport</b>	Single Magnetic Charging Port USB C Charge	-----	-----	-----	35.5x21.9x9.6 mm/ 1.40x.86x.38in	-----	-----	----	----	-----	22/.78	----	15.95 GY
<b>MCC3 USB C Reel Charging Cable Organizer</b>	-----	-----	-----	-----	21.5/.85	-----	48/1.89	----	----	-----	40/1.41	----	14.95 BL
<b>Omino</b>	4 Port Charger USB C Charge	-----	-----	-----	231x56x13.3 mm/ 9.09x2.20x.52in	-----	-----	----	----	-----	184/6.49	----	45.95 BK, WH, OR, BL, CC
<b>Ostring</b>	USB-A to 5 Port Charger	-----	-----	-----	2.5m/98.43in	-----	-----	----	----	-----	65/2.29	----	29.95 BK
<b>Obag Sport SPL</b>	-----	-----	-----	-----	-----	-----	-----	----	----	-----	-----	----	19.95 BL
<b>Obag Bike-ST Saddle Bag</b>	-----	-----	-----	-----	18x8x9cm/ 7.09x3.15x3.54 in	-----	-----	----	----	-----	105/3.70	----	15.95 BK

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
<b>Obag EDCM Tactical Bag</b>	----- -----	-----	-----	-----	191/7.52	<b>Width</b> 127/5.0	Height 61/2.52	----	----	----	245/8.64	----	19.96 BN
<b>Obag EDCS Tactical Bag</b>	----- -----	-----	-----	-----	155/5.98	<b>Width</b> 100/3.93	Height 44/1.73	----	----	----	135/4.76	----	19.95 BN
<b>Olight Opry - Multi Tool Prybar</b>	<b>Body TC4 Titanium</b> -----	-----	-----	-----	116.8/4.6	<b>Width</b> 21.6/0.85	Height 10.9/0.43	----	----	----	55/1.94	----	49.95 Ti
<b>Olight Opry Pro Titanium Multi Tool Prybar</b>	<b>Body TC4 Titanium Alloy</b> -----	-----	-----	-----	70/2.76	<b>Width</b> 26/1.02	Height 11.8/0.46	----	----	----	46.5/1.64	----	54.95 Ti

<u>Model</u>	<u>Battery/Charge</u>	<u>Lumens (Run Time)</u>	<u>Candela</u>	<u>Throw Meters/Feet</u>	<u>Length mm/in</u>	<u>Head Dia mm/in</u>	<u>Body Dia mm/in</u>	<u>Power SW Tail/Side/Both</u>	<u>Strobe</u>	<u>Proximity Sensor</u>	<u>Weight gr/oz</u>	<u>IPX</u>	<u>Price-Color</u>
--------------	-----------------------	--------------------------	----------------	--------------------------	---------------------	-----------------------	-----------------------	--------------------------------	---------------	-------------------------	---------------------	------------	--------------------

Color Codes: 5OD-Facebook 5th Anniversary Edition in OD Green AB-Antique Bronze(or Vintage Copper) ABC-(Black Diamond Gift) Antique Burgundy Camo ABL-Aqua Blue ANB-Ancient Bamboo (Aged Pure Copper) BB-Brass Bark BK-Black BKS-Black with Blue Curling Stripe BL-Blue BN-Brown BR-Brass BRD-Brick Red CA-Camouflage CB-Coral Blue CC-Cyber Cyan CCF-Carbon Fiber CG-Christmas Green CLB-Clay Beige CLG-Clover Gradient CR-Christmas Red CU-Copper DC-Desert Camouflage DB-Deep Sea Blue DP-Dragon and Phoenix DR-Dark Red DS-Desert Sunset DT-Desert Tan ER-Ember Red FG-Forest Gradient GC-Grey Camouflage GG-Gunmetal Grey GN-Green GY-Grey GYL-Golden Yellow LB-Lake Blue LC-Lava Camouflage LG-Lime Green MBK-Matte Black MBL-Midnight Blue MG-Mint Green MS-Mountain Sky NW- Night Wolf OC-Ocean Camouflage OD-OD Green OG- Olive Green OR-Orange PB-Pixel Blue PE-Patriotic Edition PG-Purple Gradient PC-Pink Camouflage PK-Pink PL-Rosy Plum PU-Purple RB-Royal Blue RD-Red RRG-Rose Red Gradient SB-Sapphire Blue SD-Stardust SG-Scarlet Gradient SI-Silver SS-Starry Sea SST-Stainless Steel S&S-Stars and Stripes Ti-Titanium TiD-Titanium Damascus UV(BM)-Ultra Violet Light in Blue Body with Magneta Dots UV(OD)-Ultra Violet Light in OD Green Body VR-Volcanic Red WH-White YL-Yellow ZD-Zirconium Damascus ZDSS-Zirconium Damascus Dark Space Silver ZG-Zombie Green ZR-Zirconium

Notes: (1) Dotted line (-----) means no information available, (2) For safety reasons, keep all lights that have a Lockout Mode, in Lockout Mode while not in use or in storage, (3) Be aware that lights with lower Lumens can have a larger Throw due to Lens and Reflector designs. Do not assume that a light with a higher Lumen output has a brighter looking output. It is the Candela output that represents the brightness output. Also note that lights with the same or close Candela Output but have a higher Lumen Output will have a brighter Flood Spill.

i1R 2 EOS Note: The output brightness will decrease as the battery power decreases. The running time is the time when the brightness attenuates to 50% of the initial value after the battery is fully charged.

i3E EOS Note: The Older 2017 Model has a different design in the head area than the newer model, but all the specs are the same, in both the size, weight and output.

Finishes Available in Different Color Temperature Options are Designated with the following abbreviations after the Color Finish - WW (2700-3700K), NW (4000-5000K), CW (5700-6700K)

LEP stands for Laser Excited Phosphor. This means that instead of an LED module that emits light directly out the front, it uses a blue laser that is first “bounced” off of a piece of phosphor and the the white light emitted is directed out the front via a series of lenses.

All Lights listed using the MCC1A USB charging cable, can also use the newer MCC3 (1/1.5/2A) USB charging cable. If the MCC3 Charging Indicator is blinking between Red and Green, try using the original cable that came with the light. Some lights that came with MCC or MCC1A can only be charged with the original charging cable, due to the older charging circuits built into those lights.

All Specifications in this chart are from Olight User Manuals, the Official Olight Websites and from Doctor Memory's Olight Manuals and Datasheet Library Website <http://drmemory.com/Olight/>. Some Specifications are missing and/or may be incorrect due to web page, manuals or spec sheets with conflicting information, misprints or wrong data being overlooked.