






S2A BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

MAX OUTPUT	MAX RUNTIME	MAX THROW
		
550 lumens	50 days	110 meters

	
TIR lens	Timer



S2A BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT



MARKET APPLICATIONS

outdoors, household

S2 Baton Black UPC: 6926540918480

S2 Baton Blue UPC: 6926540918497

S2 Baton Yellow UPC: 6926540918503

S2 Baton Gray UPC: 6926540918510

MSRP: \$ 49.95

DESCRIPTION

The S2A Baton is a compact flashlight with a side switch and variable outputs. It uses Cree XM-L2 LED and runs on two AA batteries. Coupled with TIR lens of ultra light transmission rate, it can produce a balanced beam. The S2A Baton has five brightness levels and a strobe mode, with an output ranging from 0.5 up to 550 lumens. To improve hand holding and gripping experience, the main flashlight body is wrapped in skin safe soft silicon in black, and with various color choices - fluorescent blue/yellow/gray. Also there are blue rings on the flashlight head and the side switch.

The S2A Baton serves as a perfect choice for home and outdoor illumination.



S2A BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT



FEATURES

- Cree XM-L2 LED
- Powered by two AA batteries
- Flashlight body wrapped with skin-safe silicon material of various colors for better hand gripping experience
- Uses TIR lens of high light transmission rate resulting in a balanced beam
- Eco-friendly AL6061-T6 aluminum alloy body with anti-scratch MILSPEC type-III hard anodized finish
- Controlled by thermal protection program, the turbo mode is limited at within 3 minutes, then the brightness gradually steps down to the next brightness level
- Built-in timer: Short timer (3 minutes) or Long timer (9 minutes)

OUTPUT

FL1 STANDARD	MODE 1	MODE 2	MODE 3	MODE 4	MODE 5
	550~260 lumens	260 lumens	120 lumens	20 lumens	0.5 lumens
 <small>2*AA (1.5V Lithium Iron Battery)</small>	3 + 240 minutes	250 minutes	10 hours	80 hours	50 days
 <small>2*AA (1.5V Alkaline Battery)</small>	3 + 80 minutes	105 minutes	5.3 hours	60 hours	35 days
	110 meters				
	3,000 candela				

Also includes Strobe Mode: 10Hz


WATERPROOF
IPX 8



DROP TEST



COMPLIANCE



LENS

PMMA TIR lens

LIGHT SOURCE

Cree XM-L2 LED

DIMENSIONS

Length: 5.2in / 132mm

Bezel Diameter: 0.91in / 23mm

Weight: 1.98oz / 56 g (excluding batteries)

BODY MATERIAL

6061-T6 aluminum body with anti-scratch type-III hard anodized finish
Skin safe silicone

BATTERY SOURCE

2 x AA

WARRANTY

5 Year warranty

Visit olightworld.com/warranty

ACCESSORIES

- Lanyard
- User Manual
- 1.5V Lithium Iron Disulfide Battery x 2
- Traffic Wand (white) optional
- Traffic Wand (orange) optional

olightworld.com

All performance claims to ANSI/NEMA FL1-2009 Standard. Made in China.

© Olight 5/24/16 V1