RECHARGEABLI	VARIABLE-OUTPU		LED FLAS	<b>O</b> Shlight		G ANIA	HT®
	MC	O OLICHT	arging ca	able 🔊			
MAX	TOTAL	THROW		CAN	CANDELA WA		TERPROOF
÷Ö:						~	
1020 Iumens	60 days	153 meter				IPX8	
STANDARD	MODE 1	MODE 2		DE 3	MODE 4	1	MODE 5
342	1020 ~ 500 lumens	500 Iumens	l Iun	20 nens	12 Iumens		0.5 Iumens
	2+190 minutes	200 minutes	1	. <b>3</b> ours	120 hours		60 days
Ē	Customized 3200mAh 18650 x 1						
	1.5 meters						
<u></u>	(L) 4.17in / 106mm X (D) 0.9in / 23mm						
	3.58oz/101.5 g (INCLUDING BATTERY)						

The S2R Baton II is the upgraded version of the popular S2R Baton predecessor.

It has a compact build (5% shorter than S2R Baton) for easy grip and portability.

The light can produce a maximum output of 1,150 lumens including an upgraded TIR lens that produces a perfectly balanced beam.

It has several modes to choose from including three standard modes, turbo, moonlight, and strobe.

The S2R Baton II features a battery indicator located on the side switch so you always know when to charge. It boasts a new MCC 1A magnetic charging system to ensure faster charging in a smaller form factor.

The S2R II also features a dual direction pocket clip for enhanced everyday carry.

Features:

CW LED with a maximum output of 1,150 lumens.

Includes a 3200mAh 18650 rechargeable lithium battery which is charged magnetically through the tailcap charging cable.

Features a battery indicator located on the side switch so you know when to charge. Indicator glowing green (Battery remaining>=70 %), indicator glowing yellow(Battery remaining 15-70%), indicator glowing red (Battery remaining<=15%).

Portable faster charging MCC 1A USB charging cable provided in the package.

Brand-new TIR lens design producing a perfectly balanced beam.

Flat tailcap with a strong magnet allowing the ability to use as a hands-free work light.

Multi-function side switch with five brightness levels, plus a strobe mode.

1000 lumen rechargeable flashl flashlight aluminum led flashl		<u>small flashlight</u>	pocket led flashlight	high intensity led
GENERAL DATA				
Beam Distance (ft)	443			
Beam Distance (m)	135			
Max. Performance (lumens)	1150			
Charge type	Magnetic USB charge b	ase		
Compatible Batteries	customised 18650			

## GENERAL DATA

Light Intensity (candela)	4600
Light Form	Wide/broad hotspot. Perfect for up close illumination.
Lens / Reflector Type	TIR reflector (big, defined wide hotspot)
Mode Operation	Side Switch
Form/Size Factor	Medium size (Permanent Marker)
Series	Series S (EDC, General Use)
Unique Characteristics	<ul> <li>CW LED with a maximum output of 1,150 lumens.</li> <li>Includes a 3200mAh 18650 rechargeable lithium battery which is charged magnetically through the tailcap charging cable.</li> <li>Features a battery indicator located on the side switch so you know when to charge.</li> <li>Portable faster charging MCC 1A USB charging cable provided in the package.</li> <li>Flat tailcap with a strong magnet allowing the ability to use as a hands-free work light.</li> <li>Multi-function side switch with five brightness levels, plus a strobe mode.</li> </ul>
LIGHTING LEVELS	
LEVEL 1 (lumens)	1150
Run-time LEVEL 1	1150lumens (~400lm);
	<b>230m</b> (2m).
LEVEL 2 (lumens)	400
Run-time LEVEL 2	4h
LEVEL 3 (lumens)	120
Run-time LEVEL 3	14h
LEVEL 4 (lumens)	15
Run-time LEVEL 4	100h
LEVEL 5 (lumens)	0.5
Run-time LEVEL 5	60 days
Strobe	Yes
SOS / BEACON	No

## TECHNICAL CHARACTERISTICS

## GENERAL DATA

Waterproof	IPX8
Weight (g / oz)	98.5 / 3.47
Length (mm / in)	100 / 3.94
Head Diameter (mm / in)	23 / 0.91
Body Diameter (mm / in)	23 / 0.91
Led	Luminus SST-40 CW LED
Packaging	Carton box
Use	everyday carry , key-chain, car, camping, fishing, household, EDC, general use
Package Contents	Customized 3200 mAh 3.6V 18650 Battery×1 MCC 1A charging cable×1 User manual×1 Pouch×1 Blue pocket clip×1(installed on the flashlight) Black pocket clip×1(spare, inside the package) Lanyard (including tethering tool)×1