



i1

i2

i3S

i1 EOS - **i2 EOS** - **i3S EOS**

The Olight i1, i2, i3S series flashlights come in miniature sizes as the best elaboration for the EDC flashlight. Each flashlight is equipped with its respective single CR123A, AA, or AAA battery. With three output levels of Low-Med-High, a removable clip, and its keychain hole, the i Series is convenient every day and everywhere. These flashlights are suitable for small area lighting: dark stairs, corridor lighting, a miniature light handy for close up tasks.

	i1			i2			i3S		
FL I STANDARD	MODE 1	MODE 2	MODE 3	MODE 1	MODE 2	MODE 3	MODE 1	MODE 2	MODE 3
	180 LUMENS	40 LUMENS	4 LUMENS	75 LUMENS	20 LUMENS	2.5 LUMENS	80 LUMENS	20 LUMENS	0.5 LUMENS
	1h40min	5h10min	72h	1h30min	5h	60h	35min	8h	60h
	68m			50m			38m		
	1150cd			610cd			360cd		
	IPX-8			IPX-8			IPX-8		
	1.2m			1.2m			1.2m		



Cree XM-L LED

Cree XP-G R5 LED

Cree XP-G2 LED

1 x CR123A battery

1 x AA battery

1 x AAA battery

63.5mm / 2.5"(L)*20.3mm / 0.8"(D)

81.2mm / 3.2"(L)*17.6mm / 0.7"(D)

70.8mm / 2.8"(L)*14mm / 0.55"(D)

22.5g/0.8oz (excluding batteries)

20.5g/0.72oz (excluding batteries)

11g/0.39oz (excluding batteries)

+++ Olight i1 EOS +++



- * EDC Flashlight with removable clip
- * 1 x CR123A battery

- **newest CREE XM-L LED**
- **3 light levels :**
 - **Low @ 4 lumens (burn time: 72 hours)**
 - **Medium @ 40 lumens (burn time: 5.2 hours)**
 - **High @ 180 lumens (burn time: 1.2 hours)**
- **removable clip**
- **Practical key ring for quick and easy attachment**
- **Operation by 1 x CR123A lithium battery (included)**
- **Complies with the following standards:**
 - **IPX - 8**
 - **MIL - STD 810F**
- **Premium Type III hard anodizing (aviation aluminum)**
- **Waterproof to a depth of 2 meters**
- **Shock resistant up to a drop height of 120 cm**
- **Weight: 22.5 g**
- **Dimensions: 63.5 mm x 20.3 mm (L x D)**
- **Delivery:**
 - 1 x i1 EOS**
 - 1 x Allen key for clip (de) assembly**
 - 1 x key ring**

+++ Olight i2 EOS +++



i2 EOS



- * EDC Flashlight with removable clip
- * Size: L 81.2mm x D 17.6mm
- * 1 x AA Battery

- **newest CREE XP-G R5 LED**
- **3 light levels :**
 - Low @ 2.5 lumens (burn time: 2.5 days)
 - Medium @ 20 lumens (burn time: 5 hours)
 - High @ 75 lumens (burn time: 90 minutes)
- **removable clip**
- **Practical key ring for quick and easy attachment**
- **Operation by 1 x AA battery (included)**
- **Complies with the following standards:**
 - IPX - 8
 - MIL - STD 810F
- **Premium Type III hard anodizing (aviation aluminum)**
- **Waterproof to a depth of 2 meters**
- **Shock resistant up to a drop height of 120 cm**
- **Weight: 20.5 g**
- **Dimensions: 81.2 mm x 17.6 mm (L x D)**
- **Delivery:**
 - 1 x i2 EOS
 - 1 x Allen key for clip (de) assembly
 - 1 x key ring

+++ Olight i3 EOS +++



- * EDC Flashlight with removable clip
- * Size: L 70.8mm x D 14.0mm
- * 1 x AAA Battery

- **newest CREE XP-G R5 LED**
- **3 light levels :**
 - **Low @ 2.5 lumens (burn time: 20 hours)**
 - **Medium @ 20 lumens (burn time: 1.5 hours)**
 - **High @ 70 lumens (burn time: 40 minutes)**
- **removable clip**
- **Practical key ring for quick and easy attachment**
- **Operation by 1 x AAA battery (included)**
- **Complies with the following standards:**
 - **IPX - 8**
 - **MIL - STD 810F**
- **Premium Type III hard anodizing (aviation aluminum)**
- **Waterproof to a depth of 2 meters**
- **Shock resistant up to a drop height of 120 cm**
- **Weight: 13.2 g**
- **Dimensions: 70.8 mm x 14.0 mm (L x D)**
- **Delivery:**
 - 1 x i3 EOS**
 - 1 x Allen key for clip (de) assembly**
 - 1 x key ring**

+++ Olight i6 PALADIN +++



i6 Paladin



* Battery: 2 x CR123A/RCR123 or 1 x 18650, 1 x 17670
 * Highly water resistant to IPX-8

- **newest CREE XM-L LED**
- **2 light levels :**
 - Low @ 80 lumens (burn time: 5 hours, 50 minutes)
 - High @ 420 lumens (burn time: 1 hour)
- **Combatring for tactical use**
- **Operation by 2 x CR123A lithium batteries (included)
or 2x RCR123A or 1x 18650 battery**
- **Complies with the following standards:**
 - IPX - 8
 - MIL - STD 810F
- **Premium Type III hard anodizing (aviation aluminum)**
- **Waterproof to a depth of 2 meters**
- **Shock resistant up to a height of 150 cm**
- **Weight: 13.2 g**
- **Dimensions: 140 mm x 39.2 mm (L x D)**
- **Delivery:**
 - 1 x i6 paladin
 - 1 x belt holster
 - 1 x key ring
 - 1 x lanyard



		i6 Paladin		i1 EOS			i2 EOS			i3 EOS			
	LED	Cree XM-L LED						Cree XP-G R5 LED					
	Low-Medium-High (Lumens)	80(Low)	420(High)	4	40	180	2.5	20	75	2.5	20	70	
	Run Time(Hours)	5.8	1.0	72	5.2	1.7	60	5	1.5	20	1.5	0.7	
	Max Beam Distance	200m		68m			50m			37m			
	Peak Beam Intensity	10000cd		1150cd			610cd			350cd			
	Weight(Without Battery)	127g		22.5g			20.5g			13.2g			
	Size	140 x 39.2mm		63.5 x 20.3mm			81.2 x 17.6mm			70.8 x 14.0mm			
	Water Resistant	IPX-8											
	Impact Resistance	1.5m			1.2m								
	Battery	2 x CR123A/RCR123 or 1 x 18650, 1 x 17670			1 x CR123A			1 x AA			1 x AAA		