



Olight Technology Co., Limited

Address: 2/F East, Building A, B3 Block,
Fuhai Industrial Park, Fuyong, Bao'an
District, Shenzhen, China 518103
Tel: +86-755-81452518/81452608
Fax: +86-755-81452508
E-mail: service@olightworld.com
www.olightworld.com

深圳市欧莱特科技有限公司

地址: 深圳市宝安区福永镇福海工业区
B3区A栋二楼东
电话: 0755-81452518/81452608
传真: 0755-81452508
E-mail: service@olightworld.com
www.olightworld.com

中文

感谢您购买Olight LED Flashlight, 在使用前请详细阅读本说明书. 本说明书适用于T20/T25.

简介说明:

OLIGHT T系列是高品质专业LED光战术手电筒, 产品使用CREE公司制造的高亮度LED光源, 采用高效率恒流电路驱动, 具有3档输出亮度与暴闪模式, 断电档位记忆功能; 产品以航空级铝材构造, 表面三级硬质氧化, 高透光率防爆镜片; 手电中各衔接部位以硅胶圈密封, 具有良好的防水、防尘性能. T系列提供给您轻量化/高亮战术手电, 它适用于民用或工业照明领域, 如家用、夜间骑行、户外运动等需要强光照明的场合.

标配清单:


手电 x 1, 手电包 x 1, 挂绳 x 1, 密封圈 x 2,
硅胶开关帽 x 1, 保修卡, 说明书.

操作说明:

1. 按图Figure 1指示安装电池.
2. 按下尾部开关按键, 手电点亮, 再次按下并释放时, 手电关闭.
3. 手电点亮后, 旋松头部约1/8圈, 再次旋紧时, 输出亮度改变, 重复上述操作, 输出按低-中-高-暴闪顺序循环变化.

规格参数表:

特征	产品规格	
	T20	T25
材料	铝合金, 表面三级硬质氧化	
体积	长123毫米, 直径24毫米	长153毫米, 直径22.8毫米
重量	58克	72克
颜色	黑色	黑色
LED	Cree XP-G2	Cree XP-G2
电池类型	2节CR123A锂电池或RCR123可充锂电池	2节AA碱性干电池或镍氢可充电电池
反光杯	橘皮杯	橘皮杯
透镜	钢化加硬玻璃	钢化加硬玻璃
开关	尾部战术开关	尾部战术开关
输出亮度级及动作时间	380 流明 / 2.5小时 180 流明 / 5.3小时 10 流明 / 84 小时	250 流明 / 50分钟 120 流明 / 2.8小时 15 流明 / 108小时
特殊模式	暴闪, 10赫兹	暴闪, 10赫兹
中心光强度	6400 坎德拉	4000 坎德拉
最大射程	160米	126米
防水	IPX8	IPX8
抗冲击	1.5米	1.5米



Operator's Manual

LED FLASHLIGHT

MODEL: T20/T25
CREE XP-G2

ENGLISH

Thank you for purchasing the LED flashlights made by Olight. Please read this manual carefully before using this product (suitable for T20/T25).

Brief introduction :

The OLIGHT T Series is a high quality professional LED flashlight, it uses Cree super bright LED and high efficiency constant current drive circuit, has 3 adjustable brightness levels and strobe mode, and memory function enables the flashlight rapidly restore the latest status at the moment the flashlight turns on. Aircraft grade aluminum body, Type III hard anodizing; O-ring sealed and high transparent anti-shattering optical lens; It provides you with light weight super bright tactical light source. Ideal for use in civil or general industrial such as household, night ridding, out-door sports whenever you need a powerful light.

Packlist :

Flashlight x 1, Holster x 1 Lanyard x 1, O-ring x 2, Silicon rubber boot x 1, Warranty card, Manual.



T20



T25

Operational instruction:

1. Install the batteries as show in the Figure 1.




Figure 1

2. Press the forward switch of tail-cap, the light turns on, the light will become off when the switch is pressed then released again.
3. While the flashlight is on, loosen the light head about 1/8 of a circle then tighten it down, the output will change, if above operations are repeated, the output will change by the cycle orders " Low -> Medium -> High -> Strobe ".

Specifications :

Characteristics	Specification	
	T20	T25
Material	aluminum alloy with type III Hard Anodizing	
Dimension	123mm (L) x 24mm (D)	153mm (L) x 22.8mm (D)
Weight	58g	72g
Color	Black	Black
LED	Cree XP-G2	Cree XP-G2
Battery Type	Two CR123A lithium batteries or RCR123 rechargeable batteries	Two AA Alkaline batteries or rechargeable NiHM batteries
Reflector	Orange peel	Orange peel
Lens	Tough ultra-clear tempering glass	Tough ultra-clear tempering glass
Switch	Forward switch in tail cap	Forward switch in tail cap
Output and Run Time	380 lumens / 2h30min 180 lumens / 5h20min 10 lumens / 84h	250 lumens / 50min 120 lumens / 2h50min 15 lumens / 108 h
Special Mode	Strobe, 10 Hz	Strobe, 10 Hz
Peak Beam Intensity	6400cd	4000cd
Beam Distance	160 m	126 m
Waterproof	IPX8	IPX8
Impact resistance	1.5m	1.5m